



## STANDARD BUMP STOPS

	Travel <u>from</u> static						Solid Height				
	Static	250	500	1000	1500	2000	250	500	1000	1500	2000
BR-01	2.274	1.074	1.316	1.463	1.523	1.560	1.200	0.958	0.811	0.751	0.714
BR-03	2.624	1.208	1.526	1.706	1.769	1.806	1.416	1.098	0.918	0.855	0.818
COT58-25	2.283	1.278	1.461	1.573	1.620	1.647	1.005	0.822	0.710	0.663	0.636
COT58-30	2.283	1.049	1.296	1.451	1.511	1.547	1.234	0.987	0.832	0.772	0.736
COT58-40	2.283	0.859	1.139	1.320	1.390	1.430	1.424	1.144	0.963	0.893	0.853
COT75-40	3.015	1.567	1.828	1.981	2.042	2.078	1.448	1.187	1.034	0.973	0.937
COT75-45	3.015	1.270	1.599	1.801	1.879	1.925	1.745	1.416	1.214	1.136	1.090
COT75-55	3.015	1.073	1.363	1.584	1.674	1.726	1.942	1.652	1.431	1.341	1.289
SJBCA-15	1.960	1.175	1.294	1.375	1.411	1.434	0.785	0.666	0.585	0.549	0.526
5153-R50	0.500	0.206	0.289	0.332	0.351	0.361	0.294	0.211	0.168	0.149	0.139
5153-R75	0.750	0.267	0.402	0.468	0.494	0.512	0.483	0.348	0.282	0.256	0.238
5153-W50	0.500	0.114	0.230	0.291	0.313	0.325	0.386	0.270	0.209	0.187	0.175
5153-W75	0.750	0.157	0.329	0.413	0.444	0.469	0.593	0.421	0.337	0.306	0.281
5153-B50	0.500	0.080	0.129	0.246	0.278	0.297	0.420	0.371	0.254	0.222	0.203
5153-B75	0.750	0.088	0.186	0.321	0.365	0.394	0.662	0.564	0.429	0.385	0.356
P-BR-28	2.365	1.363	1.521	1.620	1.661	1.687	1.002	0.844	0.745	0.704	0.678
P-BR-32	2.365	1.245	1.443	1.561	1.616	1.658	1.120	0.922	0.804	0.749	0.707
P-BR-38	2.365	1.006	1.252	1.421	1.491	1.532	1.359	1.113	0.944	0.874	0.833
P-BR-47	2.365	0.814	1.065	1.248	1.324	1.369	1.551	1.300	1.117	1.041	0.996
P-BR-75	0.807	0.061	0.081	0.091	0.099	0.107	0.746	0.726	0.716	0.708	0.700
O-00163-17	1.781	0.778	1.024	1.113	1.153	1.179	1.003	0.757	0.668	0.628	0.602
O-00563-01	2.170	1.157	1.334	1.450	1.499	1.529	1.013	0.836	0.720	0.671	0.641
O-00563-02	1.424	0.642	0.791	0.889	0.930	0.955	0.782	0.633	0.535	0.494	0.469
O-00563-03	0.773	0.210	0.324	0.395	0.425	0.446	0.563	0.449	0.378	0.348	0.327
O-00563-04	1.107	0.525	0.645	0.719	0.752	0.776	0.582	0.462	0.388	0.355	0.331
O-00563-05	2.180	0.091	0.160	0.195	0.212	0.224	2.089	2.020	1.985	1.968	1.956
O-00563-06	0.908	0.433	0.525	0.588	0.620	0.641	0.475	0.383	0.320	0.288	0.267
O-00563-07	2.180	0.921	1.181	1.339	1.402	1.439	1.259	0.999	0.841	0.778	0.741
O-00563-08	1.978	0.775	0.991	1.117	1.168	1.198	1.203	0.987	0.861	0.810	0.780
O-00563-23	0.758	0.249	0.338	0.395	0.423	0.443	0.509	0.420	0.363	0.335	0.315
O-00564-01	0.949	0.241	0.393	0.476	0.511	0.535	0.708	0.556	0.473	0.438	0.414