



## RES W50 / W75 BUMP STOPS

	Travel from static						Solid Height				
	Static	250	500	1000	1500	2000	250	500	1000	1500	2000
W50	0.500	0.114	0.230	0.291	0.313	0.325	0.386	0.270	0.209	0.187	0.175
2 W50 0°	1.125	0.178	0.411	0.530	0.571	0.601	0.947	0.714	0.595	0.554	0.524
2 W50 5°	1.185	0.209	0.431	0.549	0.591	0.617	0.976	0.754	0.636	0.594	0.568
2 W50 10°	1.246	0.243	0.454	0.570	0.612	0.639	1.003	0.792	0.676	0.634	0.607
2 W50 15°	1.308	0.274	0.474	0.583	0.626	0.653	1.034	0.834	0.725	0.682	0.655
3 W50 0°	1.750	0.235	0.589	0.772	0.832	0.873	1.515	1.161	0.978	0.918	0.877
3 W50 5°	1.870	0.269	0.600	0.790	0.853	0.891	1.601	1.270	1.080	1.017	0.979
3 W50 10°	1.992	0.330	0.641	0.833	0.897	0.936	1.662	1.351	1.159	1.095	1.056
3 W50 15°	2.116	0.397	0.698	0.874	0.940	0.981	1.719	1.418	1.242	1.176	1.135
4 W50 0°	2.375	0.271	0.725	0.991	1.078	1.132	2.104	1.650	1.384	1.297	1.243
4 W50 5°	2.555	0.329	0.767	1.037	1.123	1.172	2.226	1.788	1.518	1.432	1.383
4 W50 10°	2.738	0.428	0.835	1.095	1.180	1.229	2.310	1.903	1.643	1.558	1.509
4 W50 15°	2.924	0.515	0.897	1.150	1.240	1.294	2.409	2.027	1.774	1.684	1.630
5 W50 0°	3.000	0.301	0.841	1.198	1.319	1.387	2.699	2.159	1.802	1.681	1.613
5 W50 5°	3.240	0.356	0.886	1.278	1.392	1.456	2.884	2.354	1.962	1.848	1.784
5 W50 10°	3.484	0.492	0.990	1.370	1.485	1.551	2.992	2.494	2.114	1.999	1.933
5 W50 15°	3.732	0.623	1.079	1.442	1.565	1.635	3.109	2.653	2.290	2.167	2.097
W75	0.750	0.157	0.329	0.413	0.444	0.469	0.593	0.421	0.337	0.306	0.281
2 W75 0°	1.625	0.262	0.606	0.772	0.836	0.879	1.363	1.019	0.853	0.789	0.746
2 W75 5°	1.685	0.268	0.621	0.795	0.856	0.892	1.417	1.064	0.890	0.829	0.793
2 W75 10°	1.746	0.271	0.608	0.799	0.864	0.901	1.475	1.138	0.947	0.882	0.845
2 W75 15°	1.808	0.304	0.633	0.820	0.886	0.924	1.504	1.175	0.988	0.922	0.884
3 W75 0°	2.500	0.306	0.822	1.097	1.200	1.262	2.194	1.678	1.403	1.300	1.238
3 W75 5°	2.620	0.375	0.902	1.165	1.254	1.305	2.245	1.718	1.455	1.366	1.315
3 W75 10°	2.742	0.405	0.895	1.188	1.283	1.337	2.337	1.847	1.554	1.459	1.405
3 W75 15°	2.866	0.462	0.935	1.227	1.324	1.379	2.404	1.931	1.639	1.542	1.487
4 W75 0°	3.375	0.308	1.074	1.445	1.579	1.657	3.067	2.301	1.930	1.796	1.718
4 W75 5°	3.555	0.377	1.054	1.483	1.613	1.684	3.178	2.501	2.072	1.942	1.871
4 W75 10°	3.738	0.525	1.161	1.566	1.693	1.761	3.213	2.577	2.172	2.045	1.977
4 W75 15°	3.924	0.617	1.229	1.622	1.753	1.824	3.307	2.695	2.302	2.171	2.100