



## OEM BUMP STOPS STOPS STOPS

\*\*\* ALL STATIC HEIGHTS ARE WITH NO HARDWARE \*\*\*

\*\*\* ALL STOPS ARE RUN IN A CUP 2.050" ID \*\*\*

	Static	Travel from static							Height @ Load							
		100	250	500	750	1000	1250	1500	100	250	500	750	1000	1250	1500	
<b>SPEEDTHANE</b>	COT58-25	2.250	0.818	1.302	1.512	1.593	1.638	1.667	1.689	1.432	0.948	0.738	0.657	0.612	0.583	0.561
	COT58-30	2.250	0.555	1.059	1.330	1.435	1.492	1.529	1.556	1.695	1.191	0.920	0.815	0.758	0.721	0.694
	COT58-40	2.250	0.412	0.908	1.205	1.328	1.395	1.438	1.468	1.838	1.342	1.045	0.922	0.855	0.812	0.782
	COT75-40	3.000	0.946	1.630	1.910	2.021	2.083	2.122	2.150	2.054	1.370	1.090	0.979	0.917	0.878	0.850
	COT75-45	3.000	0.687	1.334	1.678	1.820	1.897	1.944	1.978	2.313	1.666	1.322	1.180	1.103	1.056	1.022
	COT75-55	3.000	0.455	1.070	1.457	1.615	1.705	1.763	1.802	2.545	1.930	1.543	1.385	1.295	1.237	1.198
	SJBCA-15	2.000	1.066	1.336	1.469	1.526	0.410	1.586	1.605	0.934	0.664	0.531	0.474	1.590	0.414	0.395
	SJBCA-22	2.000	0.700	1.105	1.306	1.381	0.780	1.461	1.484	1.300	0.895	0.694	0.619	1.220	0.539	0.516
	SJBCA-25	2.000	0.446	0.944	1.204	1.305	1.189	1.399	1.427	1.554	1.056	0.796	0.695	0.811	0.601	0.573
<b>PENSKE</b>	BR-28	2.380	1.047	1.457	1.646	1.721	0.329	1.791	1.811	1.333	0.923	0.734	0.659	2.051	0.589	0.569
	BR-32	2.380	0.883	1.338	1.556	1.645	0.640	1.724	1.747	1.497	1.042	0.824	0.735	1.740	0.656	0.633
	BR-38	2.380	0.641	1.152	1.392	1.497	0.942	1.594	1.621	1.739	1.228	0.988	0.883	1.438	0.786	0.759
	BR-47	2.380	0.364	0.935	1.196	1.314	0.220	1.426	1.455	2.016	1.445	1.184	1.066	2.160	0.954	0.925
<b>OHLINS</b>	00563-01	2.175	0.777	1.227	1.432	1.516	0.439	1.592	1.614	1.398	0.948	0.743	0.659	1.736	0.583	0.561
	00563-02	1.457	0.246	0.670	0.829	0.895	0.635	0.961	0.979	1.211	0.787	0.628	0.562	0.822	0.496	0.478
	00563-03	0.768	0.059	0.229	0.346	0.390	0.201	0.431	0.444	0.709	0.539	0.422	0.378	0.567	0.337	0.324
	00563-04	1.102	0.152	0.522	0.662	0.715	0.375	0.766	0.781	0.950	0.580	0.440	0.387	0.727	0.336	0.321
	00563-05	0.344	0.017	0.036	0.073	0.107	0.543	0.143	0.154	0.327	0.308	0.271	0.237	-0.199	0.201	0.190
	00563-06	0.915	0.212	0.470	0.562	0.602	0.173	0.645	0.658	0.703	0.445	0.353	0.313	0.742	0.270	0.257
	00563-07	2.185	0.295	0.927	1.216	1.326	0.342	1.427	1.455	1.890	1.258	0.969	0.859	1.843	0.758	0.730
	00563-08	1.969	0.226	0.748	1.007	1.097	0.484	1.178	1.200	1.743	1.221	0.962	0.872	1.485	0.791	0.769
	00563-23	0.738	0.062	0.245	0.359	0.398	0.104	0.438	0.450	0.676	0.493	0.379	0.340	0.634	0.300	0.288
	00564-01	0.925	0.073	0.222	0.400	0.460	0.201	0.512	0.528	0.852	0.703	0.525	0.465	0.724	0.413	0.397
	05375-16	0.394	0.079	0.167	0.225	0.247	0.298	0.272	0.281	0.315	0.227	0.169	0.147	0.096	0.122	0.113

